

DİYAFRAMLI VALFLER DIAPHRAGM VALVES

SELENOİD DİYAFRAMLI VALF SELENOID DIAPHRAGM VALVE

MODEL P-P85



2/2 NORMALDE KAPALI-DİYAFRAMLI TİP-PİLOT KUMANDALI 2/2 NORMALLY CLOSED – DIAPHRAGM TYPE PILOT OPERATE	
MİNİMUM ÇALIŞMA BASINCI MINIMUM OPERATING PRESSURE	0,25 BAR
AKIŞKANLAR FLUIDS	Su-Hava-Hafif yağlar Water- Air- light oils
İÇ PARÇALAR INTERNAL COMPONENTS	PASLANMAZ / STAINLESS
GÖVDE / BODY :	BRONZ / BRONZE
SIZDIRMAZ / SEAL:	EPDM-NBR-FPM- EPDM/KTW

MAKSİMUM ÇALIŞMA SICAKLIKLARI MAX. OPERATING TEMPERATURE				
NBR	EPDM	FPM	EPDM-KTV	ORTAM
90°	130°	150°	130°	80°

BOBİN VOLTAJLARI / BOBIN VOLTAGES		ÇEKİLEN GÜÇ ELECTRIC POWER		
VOLTAJ VOLTAGE		Durağan Stationary	Hareketli Moving	
V ~	12 24 48 110 230 400	50 60 Hz	11 VA	14,5 VA
V =	12 24 48 110		9 W	

ÖLÇÜLER VE TEKNİK AÇIKLAMA DIMENSIONS AND TECHNICAL EXPLANATION						
BAĞLANTI CONNECTION	ORİFİS ORIFICE	KOD CODED	DEBİ FLOW RATE	BASINÇ PRESSURE		AĞIRLIK WEIGHT
Giriş-Çıkış Inlet-Outlet	Ømm		kv m³/h	AC- Bar	DC- Bar	Kg
1/4"	10	8512	1,86	10	10	0,500
3/8"	10	8513	1,86	10	10	0,450
1/2"	12	8514	2,10	10	10	0,400

SELENOİD DİYAFRAMLI VALF SELENOID DIAPHRAGM VALVE

MODEL P-P86



2/2 NORMALDE KAPALI-DİYAFRAMLI TİP-PİLOT KUMANDALI 2/2 NORMALLY CLOSED – DIAPHRAGM TYPE PILOT OPERATE	
MİNİMUM ÇALIŞMA BASINCI MINIMUM OPERATING PRESSURE	0,3 BAR
AKIŞKANLAR / FLUIDS :	Su-Hava-Hafif yağlar Water-Air-Light oils
İÇ PARÇALAR INTERNAL COMPONENTS:	PASLANMAZ / STAINLESS
GÖVDE/ BODY:	BRONZ / BRONZE
SIZDIRMAZLIK / SEAL::	EPDM-NBR-VİTON-EPDM/KTW

MAKSİMUM ÇALIŞMA SICAKLIKLARI MAX. OPERATING TEMPERATURES				
NBR	EPDM	VİTON	EPDM-KTV	ORTAM MEDIUM
90°	130°	150°	130°	80°

BOBİN VOLTAJLARI BOBIN VOLTAGES		ÇEKİLEN GÜÇ ELECTRIC POWER		
VOLTAJ VOLTAGE		Durağan Stationary	Hareketli Moving	
V ~	12 24 48 110 230 400	50 60 Hz	11 VA	24 VA
V =	12 24 48 110		16 W	

ÖLÇÜLER VE TEKNİK AÇIKLAMA DIMENSIONS AND TECHNICAL EXPLANATION						
BAĞLANTI CONNECTION	ORİFİS ORIFICE	KOD CODE	DEBİ FLOW RATE	BASINÇ PRESSURE		AĞIRLIK WEIGHT
Giriş-Çıkış Inlet-Outlet	Ømm		kv m³/h	AC- Bar	DC- Bar	Kg
1/2"	12	8614	2,10	10	10	0,500
3/4"	20	8615	5,70	10	10	0,800
1"	25	8616	9,60	10	10	1,100
1 1/4"	32	8617	22,00	10	10	2,500
1 1/2"	39	8618	27,00	10	10	3,000
2"	51	8619	35,00	10	10	4,600
2 1/2"	65	8620	63,00	10	10	9,400
3"	75	8621	83,00	10	10	11,230

PNÖSAN San ve Tic. Ltd. Şti.

Merkez : Cemaliye Mah.Gazi Çeşme Sok.No:2/A 59860 Çorlu / TEKİRDAĞ Tel:(+90 282) 652 94 86 Pbx Fax:(+90 282) 652 74 05

Fabrika : Zafer Mah.Şehit Yzb.Yücel Kenter Cad. Blok 7 No:1-2-3 Çorlu/Tekirdağ

www.pnosan.com / bilgi@pnosan.com / satis@pnosan.com