

Ø63 MM. Bİ-METAL TERMOMETRELER BI-METAL THERMOMETERS

MODEL P-BİT



ARKADAN BAĞLANTILI / BACK CONNECTION

MONTAJ TİPİ / INSTALLATION TYPE	-		
ÖLÇÜ BİRİMİ / MEASURE UNIT	°C		
ÖLÇÜ ARALIĞI / MEASURE RANGE	-30...+60	0...+250	0...+500
	0...+120	0...+300	
	0...+160 0...+200	0...+350 0...+400	
GÖVDE / BODY	SAÇ KROMAJLI / CHROME PLATED TIN		
KAPAK / BONNET	SAÇ KROMAJLI / CHROME PLATED TIN		
GÖRÜNÜM LEVHASI / SCREEN	AKRİLİK / ACRYLIC		
İBRE / INDICATOR	0/120...160 C PLASTİK / PLASTIC 0/200...500 C ALÜMİNYUM / ALUMINIUM		
Bİ-METAL	PASLANMAZ / STAINLESS AISI-316		
TERMOVİL	PASLANMAZ / STAINLESS AISI-316		
BAĞLANTI / CONNECTION	1/2" NPT		

Ø100 / 160 MM. DİREKT BAĞ. CİVA DOLGULU TERMOMETRELER Ø100 / 160 MM. DIRECT CONNECTION THERMOMETERS WITH QUICK SILVER FILLING

MODEL P-CDT



ARKADAN BAĞLANTILI / BACK CONNECTION

MONTAJ TİPİ INSTALATION TYPE	ALTTAN VEYA ARKADAN BOTTOM OR BACK		
ÖLÇÜ BİRİMİ MEASURE UNIT	°C		
ÖLÇÜ ARALIĞI MEASURE RANGE	-40...+60	0...+250	0...+500
	0...+120	0...+300	
	0...+160 0...+200	0...+350 0...+400	
GÖVDE / BODY	PASLANMAZ / STAINLESS AISI-304		
KAPAK / BONNET	PASLANMAZ / STAINLESS AISI-304		
GÖRÜNÜM LEVHASI SCREEN	AKRİLİK / ACRYLIC		
İBRE / INDICATOR	AYARLI PASLANMAZ ADJUSTABLE STAINLESS		
KADRAN / SCALE	-		
SICAKLIK ELEMANI TEMP. ELEMENT	-		
KAPİLER BORU CAPILLARY TUBE	-		
BAĞLANTI CONNECTION	1/2" NPT		



ALTTAN BAĞLANTILI
BOTTOM CONNECTION